

Concrete Roof

Jeil Sugar Company Incheon 2004

Jeil Sugar Company Incheon 1st factory	Date	O
Applied concrete roof for water-proofing and insulation		
Applied Styrofoam on the roof for insulation. Some parts damaged.		
Damaged parts leak water. In summer when temperature is high, it smells awful.		
Removed Styrofoam and cleaned with water.		
After drying out, applied SP INTERLOCK / INNERSEAL ® twice		
Applied SUPERBASE (HS) ® (50 micron) once		
Applied SUNSHIELD ® (50 micron) once		
Applied SUPERTHERM ® (250 micron) once		
Applied ENAMOGRIP ® (100 micron) once		

[SUPERTHERM](#)® provides the added environmental benefit of a reduced [HEAT ISLAND EFFECT](#).



SP INTERLOCK / INNERSEAL

SP INTERLOCK / INNERSEAL



SUPERBASE



SUN SHIELD



SUPERTHERM



ENAMO GRIP

Company Incheon 1st factory

Date

O

concrete roof for water-proofing and insulation

polyfoam on the roof for insulation. Some parts damaged.

damaged parts leak water. In summer when temperature is high, it smells awful.

ed **SUPERTHERM**® twice (100 micron)

ed **ENAMOGrip**® (50 micron) once



1. Before application



2. SUPERTHERM



3. SUPERTHERM



4. ENAMOGRIP

Pictures from top-left

1. Before application; 2. Applying 1st [SUPERTHERM](#)® 3. Applying 2nd [SUPERTHERM](#)®
4. Applying [ENAMOGRIP](#)® (Final)