

Concrete Roof

Jeil Sugar Company Incheon
2004

SP INTERLOCK / INNERSEAL®

Company	Jeil Sugar Company Incheon 1st factory	Date	Oct 19-23, 2004
Application Area	Outdoor concrete roof for water-proofing and insulation		
Problem	Used Styrofoam on the roof for insulation. Some parts damaged. The damaged parts leak water. In summer when temperature is high, it smells awful.		
Application done	1. Removed Styrofoam and cleaned with water. 2. After drying out, applied <u>SP INTERLOCK / INNERSEAL</u>® twice 3. Applied <u>SUPERBASE</u>® (50 micron) once 4. Applied <u>SUNSHIELD</u>® (50 micron) once 5. Applied <u>SUPERTHERM</u>® (250 micron) once 6. Applied <u>ENAMOGRIP</u>® (100 micron) once		



Pictures from top left

1. Before application; 2. Applying **SP INTERLOCK / INNERSEAL**® ; 3. Applying **SP INTERLOCK / INNERSEAL**® ; 4. Applying **SUPERBASE**® ; 5. Applying **SUNSHIELD**® ; 6. Applying **SUPERTHERM**® ; 7. Applying **ENAMOGRIP**® (Final)

Company	Jeil Sugar Company Incheon 1st factory	Date	Oct 20-23, 2004
Application Area	Outdoor container (used as office) for water-proofing and insulation		
Problem	In summer, the container indoor temperature rises above 40C. Leaks when it rains.		

Application done

1. Applied **SUPERTHERM**® twice (100 micron)
2. Applied **ENAMOGRIP**® (50 micron) once



SUPERTHERM



SUPERTHERM



ENAMOGRIP

Pictures from top-left

1. Before application; 2. Applying 1st **SUPERTHERM**® 3. Applying 2nd **SUPERTHERM**® ; 4. Applying **ENAMOGRIP**® (Final)